



PORSCHE

Driving in its purest form

Coupe





The fresh-air vent below the panoramic windshield furnishes fully controlled ventilation to the passenger compartment.

In addition to the many technical improvements found in the



A pleasant blend of convenience and beauty is found in the Cabriolet with


Its convertible soft top — representative and persuasive in its sporty
elegance. The sloping section of the top with the rear-window folds inward by
simply opening a zip fastener. This semi-open tog gives refreshing ventilation
in warm weather without the wind associated with the open convertible.
Roadholding is always the criterion for judging the sports car. The proposition is supreme in this respect at any speed and especially in critical situations.






All models for 1962 have a new redesigned instrument panel with improved instrument positions.

The fuel filler pipe located in the right front fender is a practical improvement on all left-hand drive models.







Standard Equipment

INSTRUMENTS
Speedimenter with task mineage and trip mineage
Tachmenter
Tachme

A C C E S S O R I E S Ash tray Cushioned dashboard



For the Coupe and the Cabriolet,
with removable top an electrically
steel sun roof can be supplied upon request.
Its advantages are obvious: fresh air and sunshine

The fuel tank has been completely redesigned



greatest obvious change with its larger engine compartment cover on the Coupe. wo ventilation grills for the engine
are standard on all moder
ger rear window of the Coupe brings

a decided improvement in rear vision.



		Coupe, Cabrid Type 356 B / 6	Coupe, Cabriolet Type 356 B / 60		Coupe, Cabriolet Type 356 B / S		Coupe, Cabriolet Type 356 B / 90	
	Engine							
	Туре	Four-cycle fo	ur-cylinder carburator	engine in flat fou	r arrangement with ou	erhead val	ves	
data	Bore	Four-cycle, four-cylinder carburetor engine in flat four arrangement, with 3.25 in (82,5 mm) 3.25 in (82,5 mm)				3,25 in (82,5 mm)		
	Stroke	2,91 in (74,0 mm)		2.91 in (74,0 mm)		2,91 in (74,0 mm)		
	Displacement	1582 cc (96.5 cu. in)		1582 cc (96.5 cu.in)			(96.5 cu. in)	
		7.5:1		8.5:1		9:1		
	Compression ratio	60 HP at 4500 rpm		75 HP at 5000 rpm		0.000	at 5500 rpm	
	Horsepower (DIN) Max. Torque (DIN)	81 ft. lb. (11,2 mkg)		86 ft. lb. (11,9 mkg)		89 ft. lb. (12,3 mkg)		
	Max. Torque (DIN)	1000				at 4300 rpm		
	T	at 2800 rpm at 3700 rpm Four fully synchronized forward speeds and one reserve gear					· piii	
	Transmission	그 가게 있는 얼마를 하는 아이를 하는 것이 되었다. 그는 그는 그는 그는 것은 것은 것이 없는 것이 없다고 있다고 있는데 그 없다.						
	Gear ratios		urope		urope	1004040		
		1st	1:3,09 (11:34)	1st	1:3,09 (11:34)	1st	1:3,09 (11:34	
		2nd	1:1,765 (17:30)	2nd	1:1,765 (17:30)	2nd	1:1,765 (17:30	
		3rd	1:1,13 (23:26)	3rd	1:1,13 (23:26)	3rd	1:1,13 (23:26	
		4th	1 : 0,815 (27 : 22)	4th	1:0,815 (27:22)	4th	1:0,852 (27:23	
		4th (USA)	1:0,852 (27:23)	4th (USA)	1:0,852 (27:23)			
		Reverse	1:3,56	Reverse	1:3,56	Hevers	e 1:3,56	
	Body							
	Frame	Pressed thin walled sections welded to body						
	Front suspension	Dual trailing arm suspension links with anti-roll bar						
	Front springs	Two laminated square section torsion bars transversely mounted						
	Rear suspension	Swinging half axles moving about a diagonal axis						
	Rear springs	One round section torsion bar per wheel transversely mounted						
	Shock absorbers	Double acting telescopic shock absorbers front and rear						
	Service brake	Hydraulic						
	Wheels	Steel disc with deep center rim 4,5 J x 15						
	Tires	5,60×15 Sport		5,60×15 Sport			Braced tread	
	Tire pressure	Normal driving	T-1	Normal driving	•		l driving	
		front 19 psi (1,	20000000	front 19 psi (1	(3 atū)	front 23	3 psi (1,6 atů)	
					70.00 (1.00.00)			
		rear 23 psi (1,6	CONTRACTOR OF THE PARTY OF THE	rear 23 psi (1	,6 atū)		psi (1,8 atū)	
		Fast or Sport	driving	Fast or Sport	,6 atū) driving	Fast or	psi (1,8 atū) r Sport driving	
		Fast or Sport front 22 psi (1,	driving 5 atū)	Fast or Sport front 22 psi (,6 atů) driving 1,5 atů)	Fast or front 26	psi (1,8 atü) r Sport driving 5 psi (1,8 atü)	
		Fast or Sport front 22 psi (1, rear 26 psi (1,	driving 5 atū) 3 atū)	Fast or Sport front 22 psi (rear 26 psi (1	,6 atū) driving 1,5 atū) ,8 atū)	Fast or front 26	psi (1,8 atū) r Sport driving	
	Fuel tank capacity Dimensions	Fast or Sport front 22 psi (1, rear 26 psi (1,	driving 5 atū)	Fast or Sport front 22 psi (rear 26 psi (1	,6 atū) driving 1,5 atū) ,8 atū)	Fast or front 26	psi (1,8 atü) r Sport driving 5 psi (1,8 atü)	
		Fast or Sport front 22 psi (1, rear 26 psi (1,	driving 5 atū) 3 atū) gal. of which 1,6 gal. a	Fast or Sport front 22 psi (rear 26 psi (1	,6 atū) driving 1,5 atū) ,8 atū) ers, 6 liters reserve)	Fast or front 26 rear 29	psi (1,8 atü) r Sport driving 5 psi (1,8 atü)	
	Dimensions	Fast or Sport front 22 psi (1, rear 26 psi (1,1 Total of 13,2)	driving 5 atū) 3 atū) gal. of which 1,6 gal. a m)	Fast or Sport front 22 psi (rear 26 psi (1 ire reserve (50 lit	,6 atū) driving 1,5 atū) ,8 atū) ers, 6 liters reserve)	Fast or front 26 rear 29	psi (1,8 atū) r Sport driving 3 psi (1,8 atū) psi (2,0 atū)	
	Dimensions Wheel base	Fast or Sport front 22 psi (1, rear 26 psi (1,1 Total of 13,2 (driving 5 atū) 3 atū) gal. of which 1,6 gal. a m)	Fast or Sport front 22 psi (' rear 26 psi (1 ire reserve (50 lit 82,7" (2100 m	,6 atü) driving 1,5 atü) ,8 atü) ers, 6 liters reserve) m) m)	Fast or front 26 rear 29 82,7" 51,4"	psi (1,8 atū) r Sport driving 5 psi (1,8 atū) psi (2,0 atū) (2100 mm)	
	Dimensions Wheel base Front track	Fast or Sport front 22 psi (1, rear 26 psi (1, Total of 13,2 g 82,7" (2100 m 51,4" (1306 m	driving 5 atū) 3 atū) gal. of which 1,6 gal. a m) m)	Fast or Sport front 22 psi (' rear 26 psi (1 are reserve (50 lit 82,7" (2100 m 51,4" (1306 m	,6 atū) driving 1,5 atū) ,8 atū) ers, 6 liters reserve) m) m)	Fast or front 26 rear 29 82,7" 51,4" 50,1"	psi (1,8 atū) r Sport driving 5 psi (1,8 atū) psi (2,0 atū) (2100 mm) (1306 mm)	
	Dimensions Wheel base Front track Rear track	Fast or Sport front 22 psi (1, rear 26 psi (1, Total of 13,2 g 82,7" (2100 m 51,4" (1306 m 50,1" (1272 m	driving 5 atu) 3 atu) 3 al. of which 1,6 gal. a m) m) m)	Fast or Sport front 22 psi (1 rear 26 psi (1 are reserve (50 lit 82,7" (2100 m 51,4" (1306 m 50,1" (1272 m	,6 atū) driving 1,5 atū) ,8 atū ,8 atū mm mm mm mm mm)	Fast or front 26 rear 29 82,7'' 51,4'' 50,1" 157,7" (psi (1,8 atū) r Sport driving 5 psi (1,8 atū) pei (2,0 atū) (2100 mm) (1306 mm) (1272 mm)	
	Dimensions Wheel base Front track Rear track Length	Fast or Sport front 22 psi (1, rear 26 psi (1, 1 Total of 13, 2 to 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	driving 5 atu) 3 atu) 3 al. of which 1,6 gal. a m) m) m)	Fast or Sport front 22 psi (1 rear 26 psi (1 are reserve (50 lit 82,7" (2100 m 51,4" (1306 m 50,1" (1272 m 157,7" (4010 m	,6 atū) driving 1,5 atū) ,8 atū ,8 atū mm mm mm mm mm)	Fast or front 26 rear 29 82,7'' 51,4'' 50,1" 157,7" (psi (1,8 atū) r Sport driving 5 psi (1,8 atū) psi (2,0 atū) (2100 mm) (1306 mm) (1272 mm) (4010 mm)	
	Dimensions Wheel base Front track Rear track Length Width	Fast or Sport front 22 psi (1, rear 26 psi (1, 1 Total of 13, 2 to 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	driving 5 atu) 8 atu) pal. of which 1,6 gal. a m) m) m) m)	Fast or Sport front 22 psi (1 rear 26 psi (1 are reserve (50 lit 82,7" (2100 m 51,4" (1306 m 50,1" (1272 m 157,7" (4010 m	,6 atū) driving 1,5 atū) ,8 atū ,8 atū mm mm mm mm mm)	82,7" 51,4" 50,1" 157,7" (65,7"	psi (1,8 atū) r Sport driving 5 psi (1,8 atū) psi (2,0 atū) (2100 mm) (1306 mm) (1272 mm) (4010 mm)	
	Dimensions Wheel base Front track Rear track Length Width Height Turning circle	Fast or Sport front 22 pai (1, rear 26 psi (1, Total of 13,2 82,7" (2100 m 50,1" (1272 m 157,7" (4010 m 65,7" (1670 m Coupe, Cabri 33,5 ft (11 m)	driving 5 atu) 8 atu) pal. of which 1,6 gal. a m) m) m) m)	Fast or Sport front 22 psi (1 rear 26 psi (1 ire reserve (50 lit 82,7" (2100 m 51,4" (1306 m 50,1" (1272 m 157,7" (4010 m 65,7" (1670 m	,6 atū) driving 1,5 atū) ,8 atū ,8 atū mm mm mm mm mm)	82,7" 51,4" 50,1" 157,7" (65,7"	psi (1,8 atū) r Sport driving 5 psi (1,8 atū) psi (2,0 atū) (2100 mm) (1306 mm) (1272 mm) (4010 mm) (1670 m)	
	Dimensions Wheel base Front track Rear track Length Width Height Turning circle Weights	Fast or Sport front 22 psi (1, 1 rear 26 ps. 16,1 Total of 13,2 s. 15,1 Total of 13,2 s.	driving 5 atú) 5 atú) 9al. of which 1,6 gal. a m) m) m) m) m) m) olet 52,4 in (1330 mm)	Fast or Sport front 22 psi (1 rear 26 psi (1 ire reserve (50 lit 82,7" (2100 m 51,4" (1306 m 50,1" (1272 m 157,7" (4010 m 65,7" (1670 m	,6 atū) driving 1,5 atū) ,8 atū ,8 atū mm mm mm mm mm)	82,7" 51,4" 50,1" 157,7" (65,7"	psi (1,8 atū) **Sport driving 5 psi (1,8 atū) psi (2,0 atū) (2100 mm) (1306 mm) (1272 mm) (4010 mm) (1670 m)	
	Dimensions Wheel base Front track Rear track Length Width Height Turning circle Weights Dry weight	Fast or Sport front 22 pail (1, rear 26 psi (1,1 Total of 13,2 t 82,7" (2100 m 50,1" (1272 m 157,7" (4010 m 60,0),2" (177 m 1670 m 10,0),3,5 ft (11 m)	driving 5 atú) sa to) said: sa	Fast or Sport front 22 psi (1 rear 26 psi (1 ire reserve (50 lit 82,7" (2100 m 51,4" (1306 m 50,1" (1272 m 157,7" (4010 m 65,7" (1670 m	,6 atū) driving 1,5 atū) ,8 atū ,8 atū mm mm mm mm mm)	82,7" 51,4" 50,1" 157,7" (65,7"	psi (1,8 atū) **Sport driving 5 psi (1,8 atū) psi (2,0 atū) (2100 mm) (1306 mm) (1272 mm) (4010 mm) (1670 m)	

Dr.-Ing. h. c. F. Porsche K.-G. · Stuttgart-Zuffenhausen

Technical